

AMOHV Rack Mount



Customized rack or Cabinet design



Easy to Expand
Single Cluster Capacity Max. 257kWh



High security
LFP+BMS+Pack fire protection



Hight Voltafe Range
PCS system suitable for 1000V platform



Multiple Application
Meet all application scenarios in
the industrial and commercial fields

PERFORMANCE SPECIFICATIONS

Model	AMO144.69K_HV-S1	AMO192.92K_HV-S1	AMO225.08K_HV-S1
Battery Module	AMO16.07K_HV-S1 (51.2V314Ah,136kg)		
Number of Modules	9	12	14
Rated Energy (KWH)	144.69	192.92	225.08
Nominal Voltage	460.8	614.4	716.8
capacity(Ah)	314Ah		
Max. Charge Discharge Current(A)	157/200A		
Scalability	Up to 4 parallel		
Communication	RS485(B)-BAT/RS485(A)-PC/Canbus-Inverter		
Cycle Life	>6000 Cycles @25℃,0.5C,80%DOD, 70%EOL		
Weight(Approx) (KG)	1260kg	1680kg	1800kg
Dimension (W/D/H)(mm)	1110*780*1700mm	1110*780*1968mm	1110*780*2208mm
Charge Temperature	0℃~55℃		
Discharge Temperature	-20℃~55℃		
Storage Temperature	-40℃~55℃ @ 60%+25% relative humidity		
Installation Mode	Rack Mounting		
IP Grade	IP20		
Safety(Pack)	UN38.3,MSDS		
Safety(Cell)	UN38.3,MSDS,IEC62619,CE,UL1973,UL2054		
Protection	BMS, Breaker		
Altitude (m)	≤2000		
Humidity	5~85%RH Humidity		
Warranty	5 Years(25℃)		
Design Life	10+Years (25℃/77F)		

*Text and images correspond to the current state of technology at the time of printing. Subject to modifications. All information is without guarantee in spite of careful editing-liability excluded.