

AMOHV Rack Mount

AMOSOLAR Rack Mount Battery Series

AMO 107.5-215K_HV-S1



Flexible Configuration



Safe and Reliable



Eco-Friendly The whole module is non-toxic, non-polluting and environmentally friendly.



Quick installation, standard of 19-inch embedded designed module is comfortable for instalationand maintenance.



Intelligent BMS
It has protection functions including over-discharge, over-charge

PERFORMANCE SPECIFICATIONS

Model	AMO 107.5K_HV-S1	AMO 143.4K_HV-S1	AMO 179.2K_HV-S1	AMO 197.1K_HV-S1	AMO 215K_HV-S1
Battery Module	AMO17.92K_HV-S1 (64V280Ah)				
Number of Modules	6	8	10	11	12
Rated Energy (KWH)	107.5	143.4	179.2	197.1	215
Nominal Voltage	384	512	640	704	768
capacity(Ah)	280Ah				
Max. Charge Discharge Current(A)	140A				
Scalability	Up to 4 parallel				
Communication	RS485(B)-BAT/RS485(A)-PC/Canbus-Inverter				
Cycle Life	>6000 Cycles @25℃,0.5C,80%DOD, 70%EOL				
Weight(Approx) (KG)	1255kg	1525kg	1795kg	1922kg	2077kg
Dimension (W/D/H)(mm)	780*1100*1685	780*1100*1685	780*1100*1840	780*1650*1430	780*1650*1685
Charge Temperature	0℃~55℃				
Discharge Temperature	-20℃~55℃				
Storage Temperature	-40℃~55℃@ 60%+25% relative humidity				
Installation Mode	Rack Mounting				
IP Grade	IP20				
Safety(Pack)	UN38.3,MSDS				
Safety(Cell)	UN38.3,MSDS,IEC62619,CE,UL1973,UL2054				
Protection	BMS, Breaker				
Altitude (m)	≤2000				
Humidity	5~85%RH Humidity				
Warranty	5 Years(25℃)				
Design Life	10+Years (25℃/77F)				

*Text and images correspond to the current state of technology at the time of printing. Subject to modifications. All information is without guarantee in spite of careful editing-liability excluded.